




Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your ActionJac MJ-80-UK 20:1 today!



|                               |        |
|-------------------------------|--------|
| Capacity [Ton]                | 0.5    |
| Gear Ratio                    | 20:1   |
| Turns of Worm Per Inch Travel | 80     |
| Torque to Raise 1 lb. [in-lb] | 0.0090 |
| Lifting Screw Diameter [in]   | 0.50   |
| Screw Lead [in]               | 0.250  |
| Root Diameter [in]            | 0.332  |
| Tare Drag Torque [in-lb]      | 1      |

|                                                       |                    |
|-------------------------------------------------------|--------------------|
| Maximum Allowable Input [hp]                          | 0.17               |
| Maximum Input Torque [in-lb]                          | 8                  |
| Compression Loading Maximum Travel at 1000 lbs. [lbs] | 7.20               |
| Compression Loading Maximum Travel at Any Load [lbs]  | 8.75               |
| Maximum Worm Speed at Rated Load [rpm]                | 1140               |
| Travel Rate at 1750 rpm [in/min]                      | 22.5               |
| Maximum Load at 1750 RPM [lb]                         | 720                |
| Starting Torque                                       | 2 x Running Torque |

|                         |      |
|-------------------------|------|
| Base 0 Travel [lb]      | 2.5  |
| Per Inch of Travel [lb] | 0.20 |
| Grease [lb]             | 0.5  |