


## Bronze Acme Nut 1"-4 RH

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your Bronze Acme Nut 1"-4 RH today!



### Product Info

|                  |        |
|------------------|--------|
| Part Number      | 20104  |
| Thread Direction | RH     |
| Type             | Bronze |

### Details

|                           |       |
|---------------------------|-------|
| Lead [in]                 | 0.250 |
| Starts                    | 1     |
| Pitch [in]                | 0.250 |
| Turns Per Inch            | 4     |
| Lash (Maximum Axial) [in] | 0.010 |
| Nominal Rod Diameter [in] | 1.000 |
| Threads per Inch          | 4     |
| Thread Code               | 104   |
| Form                      | 2C    |

### Dimensions

|                 |          |
|-----------------|----------|
| B [in]          | 1.50     |
| C [in]          | 1.50     |
| E [in]          | 0.50     |
| F (n) Dia. [in] | (4) .266 |
| F BCD [in]      | 2.260    |
| G [in]          | 0.52     |
| H [in]          | 2.76     |
| J [in]          | 1.375-16 |

### Forces and Torques

|                               |       |
|-------------------------------|-------|
| Torque to Raise 1 lb. [in-lb] | 0.105 |
|-------------------------------|-------|

### Flange Part Numbers

|                            |         |
|----------------------------|---------|
| Flange No-Lash Part Number | 73275   |
| Flange Part Number         | FLG8281 |

### Weight

|                    |      |
|--------------------|------|
| Flange Weight [lb] | 0.85 |
| Nut Weight [lb]    | 0.52 |

### Performance Specifications

|                            |        |
|----------------------------|--------|
| Efficiency [%]             | 38     |
| Lead Accuracy +/- [in/in]  | 0.0003 |
| Dynamic Load Capacity [lb] | 5000   |
| Static Load Capacity [lb]  | 16000  |