


## GRV12 - 200 - S

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your GRV12 - 200 - S today!



### Product Info

|                 |                 |
|-----------------|-----------------|
| Part Number     | GRV12 - 200 - S |
| Max Stroke [mm] | 160             |

### Material Specification

|          |              |
|----------|--------------|
| Rail     | SUS440C + Ni |
| Roller   | 100Cr6       |
| Retainer | SUS304       |

### Dimensions

|         |      |
|---------|------|
| H [mm]  | 58   |
| T [mm]  | 28   |
| W [mm]  | 26.9 |
| L [mm]  | 200  |
| n [mm]  | 14   |
| P [mm]  | 100  |
| L1 [mm] | 50   |
| L2 [mm] | 1    |
| ØD [mm] | 12   |
| L3 [mm] | 130  |
| R [mm]  | 7    |
| P1 [mm] | 11   |
| P2 [mm] | 18   |
| A [mm]  | 12   |
| M       | M10  |
| d1 [mm] | 8.5  |
| d2 [mm] | 13.5 |
| B [mm]  | 8.2  |

### Performance Specifications

|                          |       |
|--------------------------|-------|
| Dynamic C [N]            | 14700 |
| Static C0 [N]            | 13187 |
| Capacity Per Bearing [N] | 4396  |

### Weight

|              |      |
|--------------|------|
| Per Rail [g] | 2262 |
|--------------|------|