

GRVP04 - 160 - S

Call 800-321-7800 or visit us online at www.nookindustries.com to configure and order your GRVP04 - 160 - S today!



Product Info

| | |
|-----------------|------------------|
| Part Number | GRVP04 - 160 - S |
| Max Stroke [mm] | 130 |

Material Specification

| | |
|----------|--------------|
| Rail | SUS440C + Ni |
| Roller | 100Cr6 |
| Retainer | POM Plastic |

Dimensions

| | |
|---------|------|
| H [mm] | 21 |
| T [mm] | 11 |
| W [mm] | 10 |
| L [mm] | 160 |
| n [mm] | 8 |
| P [mm] | 40 |
| L1 [mm] | 20 |
| L2 [mm] | 2 |
| ØD [mm] | 4 |
| L3 [mm] | 99.6 |
| R [mm] | 14 |
| P1 [mm] | 4.3 |
| P2 [mm] | 7 |
| A [mm] | 4.5 |
| M | M5 |
| d1 [mm] | 4.3 |
| d2 [mm] | 7.5 |
| B [mm] | 4.1 |

Performance Specifications

| | |
|--------------------------|------|
| Dynamic C [N] | 1230 |
| Static C0 [N] | 1170 |
| Capacity Per Bearing [N] | 390 |

Weight

| | |
|--------------|-----|
| Per Rail [g] | 254 |
|--------------|-----|