


## GRVP06 - 550 - S

Call 800-321-7800 or visit us online at [www.nookindustries.com](http://www.nookindustries.com) to configure and order your GRVP06 - 550 - S today!



| Product Info               |                  |
|----------------------------|------------------|
| Part Number                | GRVP06 - 550 - S |
| Max Stroke [mm]            | 458              |
| Material Specification     |                  |
| Rail                       | SUS440C + Ni     |
| Roller                     | 100Cr6           |
| Retainer                   | POM Plastic      |
| Dimensions                 |                  |
| H [mm]                     | 31               |
| T [mm]                     | 15               |
| W [mm]                     | 14               |
| L [mm]                     | 550              |
| n [mm]                     | 22               |
| P [mm]                     | 50               |
| L1 [mm]                    | 25               |
| L2 [mm]                    | 2                |
| ØD [mm]                    | 6                |
| L3 [mm]                    | 326.5            |
| R [mm]                     | 36               |
| P1 [mm]                    | 5.4              |
| P2 [mm]                    | 9                |
| A [mm]                     | 6                |
| M                          | M6               |
| d1 [mm]                    | 5.3              |
| d2 [mm]                    | 9.5              |
| B [mm]                     | 5.2              |
| Performance Specifications |                  |
| Dynamic C [N]              | 2570             |
| Static C0 [N]              | 2632             |
| Capacity Per Bearing [N]   | 877              |
| Weight                     |                  |
| Per Rail [g]               | 1691             |